Offline Help Files

6.02 Offline Special Commands

The special commands that can be used with Offline are as follows:

- **/js:<Javascript code>:** Executes the specified Javascript code. Used as a command tool. Some examples are as follows:

  ```
  /js:1+2
  /js:Math.max(1,2,3)
  /js:this.m_CurrentTransaction.m_ConnectionName
  ```

- **/jsf:<Javascript filename> [:<Transaction name>]:** Loads a file and runs a transaction. If the transaction name is the same as the Javascript file name, the transaction will be run immediately. If multiple transactions are defined in a single Javascript file, user can specify a transaction name following the Javascript file name. See the following examples:

  ```
  /jsf:mm01
  /jsf:wkdr:mm01
  ```

- **/n<Transaction Code>_stat:** Enables a user to view the transaction's status screen by displaying the local database table. See the examples below:

  ```
  /mm01_stat //Displays status for the MM01 transaction.
  /nlogon_stat //Displays the logon table
  /nsession_stat //Displays the Session table
  ```

Unique solution ID: #2075
Author: sarvani.kusuri@guixt.com
Last update: 2021-06-03 18:24

(c) 2026 Liquid UI | Synactive | GuiXT <dev@guixt.com> | 2026-10-08 12:06
URL: https://www.liquid-ui.com/knowledge_base/content/137/1072/en/602-offline-special-commands.html